

SXBlue GPS Rugged, Bluetooth sub-meter GPS and SBAS receiver

from GENEQ



FEATURES

GPS and SBAS

The SXBlue is a compact GPS and SBAS module that offers sub-meter performance suitable for a variety of applications including Forestry, Mining, Machine Navigation, Precision Agriculture, GIS and Mapping, at a price that you can afford.

Bluetooth Enabled

The SXBlue provides a wireless link with any Bluetooth enabled PDA, computer or device, thus eliminating the need for cumbersome cabling.

High Performance GPS

The SXBlue delivers sub-meter positioning accuracy, low power consumption and optional 2, 10 or 20Hz position update rates.

It uses a new GPS engine architecture that provides faster startup and acquisition times. With a current almanac and ephemeris, the SXBlue will provide a position within 35 seconds. If it's been powered within the last couple hours, the SXBlue will provide a position within approximately 20 seconds.

SBAS Support

The US Federal Aviation Administration's Wide Area Augmentation System (WAAS) is now undergoing rigorous final testing for its Initial Operation Capability. Other WAAS-compatible Space Based Augmentation Systems (SBAS) are also under development elsewhere such as the European Geostationary Navigation Overlay System (EGNOS) and the Japanese MTSAT Satellite-based Augmentation System (MSAS), among others. The SXBlue provides compatibility for each of these free services.

Interface

The SXBlue features a Bluetooth and an RS-232 serial ports, both of which may be independently configured for versatility. For example, both ports might be set to output either NMEA 183 or RTCM-104. The RS-232 might be configured for RTCM-104 input.

A series of LED on the front panel provides useful monitoring information such as Power, GPS, DGPS, SBAS Lock and Bluetooth connection.

COAST™ Technology

COAST™ Technology allows the SXBlue to use old correction data for up to 45 minutes or more without seriously affecting the quality of your positioning. Using COAST™, the SXBlue is less likely to be affected by differential outages due to differential signal blockages, weak signal, or interference. No other product offers this flexibility.

SPECIFICATIONS

GPS Sensor	
Receiver Type	L1, C/A code, with carrier phase smoothing
Channels	12-channel, parallel tracking
WAAS Tracking	2-channel parallel tracking
Update Rate	1 Hz default, 5Hz optional
Horizontal Accuracy	<60m 95% confidence (DGPS) 1 <2,5m 95% confidence (no SA) 2
Cold Start	60s (no almanac or RTC) 3
Warm Start 1	45s (valid almanac, no RTC)
Warm Start 2	35s (valid almanac and RTC)
Hot Start	20s (valid almanac, RTC, and <2 hours since last fix)
Reacquisition	<1s
Maximum Speed	1607 km/h (999 mph)
Maximum Altitude	18,288m (60,000 ft)
Communication	
Serial ports	1 Bluetooth serial port (9600 baud) 1 full duplex RS-232C
Baud Rates	4800 to 57600
Data I/O Protocol	NMEA 183
Raw Measurement Data	Proprietary binary (RINEX utility available)
Correction I/O Protocol	RTCM SC-104
Status LEDs	Power, GPS lock, DGPS position, SBAS lock, Bluetooth connection
Bluetooth	
Bluetooth Transmission	Class 1
Frequency	2.400 – 2.485 GHz
Max Transmit Power	+6 dBm
Min Transmit Power	+0 dBm
Range	35 m
Fully Bluetooth pre-qualified	Bluetooth 1.1
Power	
Input Voltages	5 VDC (4.5 to 9 VDC), or 12 VDC (9 to 18 VDC, or 24 VDC (18 to 36 VDC)
Average Power Consumption	3.6 W @ 7.2 V
Average Current Consumption	865 mA @ 5 V 270 mA @ 12 V 125 mA @ 24 V
Antenna Voltage Output	5 VDC
Antenna Input Impedance	50 Ω

Environmental	
Operating Temperature	-40°C to +70°C
Storage Temperature	-40°C to +85°C
Humidity	95% non-condensing
Mechanical	
Enclosure material	Environmentally sealed powder-coated Aluminum
Enclosure rating	IP65, NEMA4X, DIN VDE 0470
Enclosure Dimensions	11.26cm x 8.54cm x 3.53cm (4.43" x 3.36" x 1.39")
Overall Dimensions	14.20cm x 8.54cm x 3.53cm (5.59" x 3.36" x 1.39")
Weight	268g (.6 lbs)
Mounting	Mounting bracket optional
Power Connector	2-pin weathertight
Data Connector	3-pin weathertight
Antenna Connector	BNC female, straight

Antenna	
GPS Frequency Range:	L1 (1575 MHz +/- 10 MHz)
Gain (without cable):	26.5 dB (+/- 2 dB), 35mA
Voltage:	+5 VDC +/- 10%
Impedance:	50 Ohms
Dimensions:	5.5 diam. x 2.2 cm (2.16 x .87 in.)
Weight (without cable):	79g (.17 lbs) (with removable magnet mount)
Antenna Connector:	SMA Female
Finish:	Fluid Resistant
Temperature:	-55oC to +85oC
Humidity:	Immersion 1 meter

NOTE

1. SVs > 5, HDOP < 2, short baseline from reference station, and low multipath environment.
2. Dependant upon ionospheric activity and multipath
3. Real-time clock